

M050 PUR-Clearcoat Gloss and M054 PUR-Clearcoat Semigloss Technical Advice Sheet

Description

Water-based, one-component protective lacquers for wood and painted interior surfaces. kt.COLOR PUR-Clearcoats protect surfaces painted Satinée paints. Coated surfaces show excellent chemical, abrasion, lotion and grease resistance. The clearcoats do not yellow and are easily cleaned. PUR-Clearcoats M050 and M054 spread well and can applied with a low-pile roller, brush applied or spray-painted.

When should you use M050 and M054 PUR-Clearcoat?

Use on highly exposed surfaces painted with our Satinée paint colors to increase their mar, abrasion and chemical resistance. Coated surfaces can be cleaned without burnishing the surface or damaging the pigments. Use for doors without handles, kitchen cabinets, behind sinks, etc.

Surface preparation

Surfaces to be coated must be dry and free of dirt, waxes or grease. Do not use below 15 ° C (surface temperature). Clean surfaces with mild soapy water and wipe dry. Do not use furniture strippers.

Application instructions

Note	stir PUR-Clearcoats well
Coverage	ca. 100 - 150 g will cover 10 sq. ft.
Dilution	use undiluted (brush or roller) or add max. 10% water (spraypaint)
Application	brush, roll or spray
Dry time	4 to 6 hours
Cleaning	Clean brush right away with soap and water

Ingredients

M050 PUR-Clearcoat Gloss: polyurethane resin 21%, water 63.8%, acrylic resin 5%, propylene glycol 6%, glycol ether DPnB 1%, PU-thickener 0.8%, wetting agents 0.3%, wax emulsion 1.5%, defoamer 0.2%, plasticizer 0.4 %.

Identification

ChemVOCFarbV Kat. A/e Wb. EU-limits: 2010 130 g/l. Contains 64 g/l VOC. No Labeling required according to GHS.

Waste disposal

Empty containers before recycling. EU Waste Code no. 08 01 12.

Safety precautions

Keep out of the reach of children. Protect eyes and skin. Provide sufficient ventilation during use and while drying.

The information given in this technical advice sheet is for guidance and is given in good faith but without warranty, since site conditions are beyond our control. We can accept no liability for the performance of the products arising out of their use beyond the value of the goods we deliver.